

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
12 January 2006 (12.01.2006)

PCT

(10) International Publication Number
WO 2006/004242 A1


- (51) International Patent Classification⁷: **B65D 83/76**
- (21) International Application Number:
PCT/KR2005/000083
- (22) International Filing Date: 11 January 2005 (11.01.2005)
- (25) Filing Language: Korean
- (26) Publication Language: English
- (30) Priority Data:
20-2004-0018524 30 June 2004 (30.06.2004) KR
- (71) Applicant (for all designated States except US): **YON-
WOO CO., LTD.** [KR/KR]; 473-5, Gajwa-dong, Seo-gu,
Incheon 404-250 (KR).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **KEE, Jung
Hyun** [KR/KR]; 81-59, Pumyang-Apartment 104-702,
Gajwa-dong, Seo-gu, Incheon 404-250 (KR).
- (74) Agent: **JOUNG, Suk Young**; 828-8, New-Seoul Building
401, Yeoksam-dong, Gangnam-gu, Seoul 135-080 (KR).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

[Continued on next page]

(54) Title: PUSH-TYPE DISPENSING DEVICE



(57) Abstract: A push-type dispensing device is disclosed. dispensing device includes an outer casing (10). A nozzle cap (20) is fastened to a lower end of the outer casing. An inner casing (30) is housed in the outer casing, contains contents, and moves vertically. A button (40) is coupled to an upper end of the inner casing and actuated to move the inner casing downwards. A dispenser (50) is coupled to a lower end of the inner casing and dispenses a prescribed amount of contents by a pumping action. An elastic spring (60) is interposed between a cylinder cap and the nozzle cap, and elastically restores the inner casing to an original position thereof. A plunger (70) is in close contact with an inner surface of the inner casing, and pushes the contents toward the dispenser when the contents are dispensed.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.